




BRPV3

Type 2 DC Surge Arrester for PV



3 Mod		BRPV3 600	BRPV3 1000	BRPV3 1500
SPD classification according to IEC61643-31 / EN61643-31		Type 2 / Class II	Type 2 / Class II	Type 2 / Class II
Max. continuous operating dc voltage	U _{cpv}	600V	1000V	1500V
Nominal discharge current (8/20μs)	I _n	20kA	20kA	20kA
Max. discharge current (8/20μs)	I _{max}	40kA	40kA	40kA
Voltage protection level [(DC+/DC-)→PE]	U _p	≤ 2.6kV	≤ 4.0kV	≤ 5.2kV
Response time	t _A	≤ 25ns	≤ 25ns	≤ 25ns
Operating temperature range	T _u	-40°C -80°C	-40°C -80°C	-40°C -80°C
Operating state/fault indication		green/red	green/red	green/red
Cross-section area (Min.)		4mm ²	4mm ²	4mm ²
Cross-section area (Max.)		35mm ²	35mm ²	35mm ²
For mounting on		35mm Din rail	35mm Din rail	35mm Din rail
Enclosure material		Thermoplastic UL94-V0	Thermoplastic UL94-V0	Thermoplastic UL94-V0
Degree of protection		IP20	IP20	IP20
Order Code		B18009	B18010	B18018
Order code (With remote signal)		B18011	B18012	B18019