




BR-25GR 2P Type 1 Surge Arrester



■ BR-25GR 2P surge arrester is suitable for single phase TN system.

		BR-25GR 150 2P	BR-25GR 275 2P	BR-25GR 320 2P
SPD classification according to EN61643-11		Type 1 + Type 2	Type 1 + Type 2	Type 1 + Type 2
SPD classification according to IEC61643-11		Class I + Class II	Class I + Class II	Class I + Class II
Nominal operating voltage	Un	120V (50/60Hz)	230V (50/60Hz)	230V (50/60Hz)
Max. continuous operating a.c. voltage	Uc	150V (50/60Hz)	275V (50/60Hz)	320V (50/60Hz)
Lightning impulse current (10/350µs)	Iimp	25kA	25kA	25kA
Nominal discharge current (8/20µs)	In	25kA	25kA	25kA
Maximum discharge current (8/20µs)	I _{max}	100kA	100kA	100kA
Quantity of electric charge	Q	12.5As	12.5As	12.5As
Specific energy	W/R	156kJ/Ω	156kJ/Ω	156kJ/Ω
Voltage protection level	Up	≤2.0kV	≤2.0kV	≤2.0kV
Short-circuit current rating a.c.	I _{sc}	25kA rms	25kA rms	25kA rms
Max. backup fuse		315A gG	315A gG	315A gG
Temporary overvoltage	TOV	440V/120min -withstand	440V/120min -withstand	440V/120min -withstand
Response time	t _A	≤100ns	≤100ns	≤100ns
Operating temperature range	T _u	-40°C-80°C	-40°C-80°C	-40°C-80°C
Cross-section area (Min.)		4mm ²	4mm ²	4mm ²
Cross-section area(Max.)		35mm ²	35mm ²	35mm ²
For mounting on		35mm Din rail	35mm Din rail	35mm Din rail
Enclosure material		Thermoplastic UL94-V0	Thermoplastic UL94-V0	Thermoplastic UL94-V0
Degree of protection		IP20	IP20	IP20
Order Code		B17124	B17137	B17150
Order Code (With remote signaling)		B17125	B17138	B17151