





BR-20 2P

Type 2 Surge Arrester

- * Thermal stability 100A without additional protection
- * Patented fast tripping mechanism



BR-20 2 pole surge arrester is suitable for TN-S system.

	BR-20 150 2P	BR-20 275 2P	BR-20 320 2P	BR-20 385 2P	BR-20 440 2P
SPD classification according to EN61643-11	Type 2	Type 2	Type 2	Type 2	Type 2
SPD classification according to IEC61643-11	Class II	Class II	Class II	Class II	Class II
Max. continuous operating a.c. voltage	Uc	150V	275V	320V	440V
Nominal discharge current (8/20μs)	In	10kA	10kA	10kA	10kA
Max. discharge current (8/20μs)	I _{max}	20kA	20kA	20kA	20kA
Voltage protection level	Up	≤0.8kV	≤1.3kV	≤1.5kV	≤1.8kV
Voltage protection level 5kA	Up	≤0.6kV	≤1kV	≤1.2kV	≤1.4kV
Max. backup fuse		63A gG	63A gG	63A gG	63A gG
Short-circuit withstand capacity	I _{SCCR}	25kA	25kA	25kA	25kA
Temporary overvoltage TOV-withstand	U _T	175V/5sec.	335V/5sec.	335V/5sec.	415V/5sec.
Temporary overvoltage TOV-safe failure	U _T	230V/120min.	440V/120min.	440V/120min.	765V/120min.
Response time	t _A	≤25ns	≤25ns	≤25ns	≤25ns
Operating temperature range	T _u	-40°C-80°C	-40°C-80°C	-40°C-80°C	-40°C-80°C
Operating state/fault indication		green/red	green/red	green/red	green/red
Cross-section area (Min.)		4 mm ²	4 mm ²	4 mm ²	4 mm ²
Cross-section area (Max.)		35mm ²	35mm ²	35mm ²	35mm ²
For mounting on	35mm Din rail				
Enclosure material	Thermoplastic UL94-V0				
Degree of protection	IP20	IP20	IP20	IP20	IP20
Order Code	B18721	B18723	B18725	B18727	B18729
Order Code (With remote signaling)	B18722	B18724	B18726	B18728	B18730