




## BR-25M 1+1

Type 1+Type 2+Type 3  
Surge Arrester



■ BR-25M 1+1 surge arrester is suitable for single phase TT and TN system.

	BR-25M 150 1+1	BR-25M 275 1+1	BR-25M 320 1+1
SPD classification according to EN61643-11	Type 1 + Type 2 + Type 3	Type 1 + Type 2 + Type 3	Type 1 + Type 2 + Type 3
SPD classification according to IEC61643-11	Class I + Class II + Class III	Class I + Class II + Class III	Class I + Class II + Class III
Nominal operating voltage	Un	120V/240V (50/60Hz)	250V/440V(50/60Hz)
Max. continuous operating a.c. voltage	Uc (L-N/N-PE)	150V/255V (50/60Hz)	275V/255V (50/60Hz)
Lightning impulse current (10/350µs)	Iimp (L-N/N-PE)	25kA/50kA	25kA/50kA
Total discharge current (10/350µs)	I <sub>total</sub>	50kA	50kA
Nominal discharge current (8/20µs)	In (L-N/N-PE)	25kA/50kA	25kA/50kA
Maximum discharge current (8/20µs)	I <sub>max</sub> (L-N/N-PE)	120kA	120kA
Combined impulse	Uoc	20kV	20kV
Quantity of electric charge (L-N,N-PE)	Q	12.5As, 25As	12.5As, 25As
Specific energy (L-N,N-PE)	W/R	156kJ/Ω, 625kJ/Ω	156kJ/Ω, 625kJ/Ω
Voltage protection level	Up (L-N/N-PE)	≤0.8kV/≤1.5kV	≤1.3kV/≤1.5kV
Short-circuit current rating a.c.	I <sub>SCCR</sub> (L-N/N-PE)	25kA rms/100A rms	25kA rms/100A rms
Max. backup fuse		200A gG	200A gG
Temporary overvoltage TOV-withstand	U <sub>T</sub> (L-N)	180V/5sec.	335V/5sec.
Temporary overvoltage TOV-safe failure	U <sub>T</sub> (L-N)	230V/120min.	440V/120min.
Temporary overvoltage TOV-withstand	U <sub>T</sub> (N-PE)	1200V/200ms	1200V/200ms
Leakage current	I <sub>PE</sub>	None	None
Response time	t <sub>A</sub>	≤25ns/≤100ns	≤25ns/≤100ns
Operating temperature range	T <sub>u</sub>	-40°C-80°C	-40°C-80°C
Operating state/fault indication		green/red	green/red
Cross-section area (Min.)		4mm <sup>2</sup>	4mm <sup>2</sup>
Cross-section area(Max.)		35mm <sup>2</sup>	35mm <sup>2</sup>
For mounting on		35mm Din rail	35mm Din rail
Enclosure material		Thermoplastic UL94-V0	Thermoplastic UL94-V0
Degree of protection		IP20	IP20
Order Code		B17210	B17223
Order Code (With remote signaling)		B17211	B17224